

HVL-F58AM



| | | Camera Body | | | | | | | | | | | | | | | | | | |
|---------------------------------------------------|-----------------------|----------------------|------------------|--------------------|----------|----------|-----------|-----------|-------------|---------------|----------------|-------------------|-------------|--------------|--------------|--------------|--------------|-------------------|--------------|-----|
| | | Konica Minolta™ | 2181 | 2186 | 2098 | 2162 | 2166 | 2165 | 2169 | 2163 | 2164 | 2153 | 2154 | 2155 | 2152 | 2089 | 2097 | 2151 | 2092 | |
| | | Japan | Alpha™-7 DIGITAL | AlphaSweet DIGITAL | Alpha-9 | Alpha-7 | Alpha-70 | Dynax™ 3L | - | Alpha-SweetII | Alpha-SweetIII | Alpha-Sweet | - | Alpha-SweetS | Alpha-807si | Alpha-707si | Alpha-507si | Alpha-303si SUPER | Alpha-303si | |
| | | Euro | Dynax 7D | Dynax 5D | Dynax 9 | Dynax 7 | Dynax 60 | Dynax 3L | Dynax 30/40 | Dynax 5 | Dynax 3 | Dynax 505Si Super | Dynax 505Si | Dynax 404Si | Dynax 800si | Dynax 700si | Dynax 600si | Dynax 500si SUPER | Dynax 500si | |
| | | USA | Maxxum® 7D | Maxxum 5D | Maxxum 9 | Maxxum 7 | Maxxum 70 | Maxxum 3 | Maxxum 50 | Maxxum 5 | Maxxum 4 | Maxxum XTSi | Maxxum HTSi | Maxxum STSi | Maxxum 800si | Maxxum 700si | Maxxum 600si | Maxxum 500si | Maxxum 400si | |
| Flash function | Compatibility | | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | |
| | Attaching | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | |
| | Burst | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Program Reset | | No | No | No | Yes | No | No | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No | Yes | Yes |
| | Flash Metering | ADI flash metering | | Yes | Yes | No | Yes | Yes | Yes | Yes | Yes | Yes | No | No | No | No | No | No | No | No |
| | | P-TTL flash metering | | Yes | Yes | No | No | No | Yes | Yes | No | No | No | No | No | No | No | No | No | No |
| | | TTL flash metering | | No | No | Yes | Yes | Yes | No | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Auto Zoom | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Flash Range Display | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | HSS (High-Speed Sync) | | Yes | Yes | Yes | Yes | Yes | No | No | Yes | No | Yes | Yes | No | Yes | Yes | Yes | No | No | |
| | Wireless/Remote HSS | | Yes | Yes | No | Yes | Yes | No | No | Yes | No | No | No | No | No | No | No | No | No | No |
| | Wireless/Remote flash | | Yes | Yes | No | Yes(*1) | Yes(*1) | Yes | No | Yes(*1) | No | No | No | No | No | No | No | No | No | No |
| | Wireless controller | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | Wireless Ratio | Controller Flash | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | | Remote Flash | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | Slow sync. | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Modeling | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Multiple flash | | Yes | Yes | Yes | Yes | Yes | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | Manual flash | | Yes | Yes | Yes | Yes | Yes | Yes(*2) | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| | AF illuminator | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Auto zoom control optimized for image sensor size | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |
| Auto WB Adjustment with Color Temperature Info | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |
| Red-Eye Reduction | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |
| FEL Lock | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |

*1 Wireless Flash function is available when shutter speed is 1/60sec. or faster.

*2 It is available by setting the recording mode that can use the manual flash mode with custom setting on the flash unit.

HVL-F58AM



| | | Camera Body | | | | | | | | | | | | | | | | | | |
|---------------------------------------------------|-----------------------|----------------------|-------------|--------------|------------|-----------------|-----------------|-----------------|------------|-------------|--------------|--------------|--------------|--------------|-------------|-------------|-------------|------------|--------------|----|
| | | Konica Minolta | 2156 | 2099 | 2181 | 2082 (2096) | 2084 (2093) | 2085 (2094) | 2095 | 2087 | 2075 | 2076 | 2077 | 2078 | 2071 | 2072 | 2073 | 2101 | 2102 | |
| | | Japan | Alpha-360si | Alpha-101si | Alpha-9xi | Alpha-7xiP /7xi | Alpha-5xiP /5xi | Alpha-3xiP /3xi | Alpha-2Xi | Alpha-SPXi | Alpha-8700i | Alpha-7700i | Alpha-5700i | Alpha-3700i | Alpha-9000 | Alpha-7000 | Alpha-5000 | Vectis S-1 | Vectis S-100 | |
| | | Euro | Dynax 303si | Dynax 300si | Dynax 9xi | Dynax 7xi | Dynax 5xi | Dynax 3xi | Dynax 2Xi | Dynax SPXi | Dynax 8000i | Dynax 7000i | Dynax 5000i | Dynax 3000i | Dynax 9000 | Dynax 7000 | Dynax 5000 | Vectis S-1 | Vectis S-100 | |
| | | USA | Maxxum QTsi | Maxxum 350si | Maxxum 9xi | Maxxum 7xi | Maxxum 5xi | Maxxum 3xi | Maxxum 2Xi | Maxxum SPXi | Maxxum 8000i | Maxxum 7000i | Maxxum 5000i | Maxxum 3000i | Maxxum 9000 | Maxxum 7000 | Maxxum 5000 | Vectis S-1 | Vectis S-100 | |
| Flash Function | Compatibility | | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Usable | Not usable | |
| | Attaching | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes (*3) | Yes (*3) | Yes (*3) | Yes | No | |
| | Burst | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No |
| | Program Reset | | No | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No | No | No | No | No | Yes | No | |
| | Flash Metering | ADI flash metering | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | | P-TTL flash metering | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | | TTL flash metering | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No |
| | Auto Zoom | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No |
| | Flash Range Display | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No |
| | HSS (High-Speed Sync) | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | Wireless/Remote HSS | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | Wireless/Remote flash | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | Wireless controller | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | Wireless Ratio | Controller Flash | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | | Remote Flash | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No |
| | Slow sync. | | Yes | Yes | Yes | Yes | Yes | No | Yes | Yes | Yes | Yes | Yes | Yes | No | Yes | Yes | No | Yes | No |
| | Modeling | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No |
| | Multiple flash | | No | No | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No | Yes | Yes | Yes | Yes | No |
| | Manual flash | | Yes(*2) | Yes(*2) | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes(*2) | Yes | Yes | Yes | Yes | No |
| | AF illuminator | | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | Yes | No | No | No | Yes | No |
| Auto zoom control optimized for image sensor size | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |
| Auto WB Adjustment with Color Temperature Info | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |
| Red-Eye Reduction | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |
| FEL Lock | | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | No | |

*2 It is available by setting the recording mode that can use the manual flash mode with custom setting on the flash unit.

*3 It is available with Flash Shoe Adapter FS-1200. (Konica Minolta made)h