

ティールスモールパラメーター Parámetros "Thiele/Small"
 Thiele/Small parameters Thiele/Small 參數
 Paramètres de Thiele-Small

	XS-L1236	XS-L1036	XS-L836	XS-L1246	XS-L1046
インピーダンス, Impedance , Impédance , Impedancia , 阻抗	4Ω	4Ω	4Ω	4Ω	4Ω
d (mm)	260	210	165	260	210
d (inch)	10.3	8.3	6.5	10.3	8.3
Rdc (Ω)	3.3	2.8	3.6	3.2	2.8
Fs (Hz)	25.6	25.4	33.85	26.1	26.8
Qts	0.36	0.33	0.45	0.37	0.36
Qes	0.39	0.35	0.48	0.40	0.39
Qms	5.18	4.69	7.26	5.11	4.96
Vas (Lit.)	66.1	51.6	14.9	56.3	47.7
Vas (Cu.ft)	3.67	1.75	0.61	3.67	1.75
Mms (g)	226.0	130.7	95.6	253.4	129.2
Lvc (mH)	1.2	1.2	1.3	1.3	1.2
Xmax (mm)	5	4.3	5.3	5	4.3
Xmax (inch)	0.2	0.17	0.21	0.2	0.17
BL (Tm)	17.5	13.0	12.4	18.4	12.6
ボックス容量 (ネット) Enclosure vol. (Net) Vol. du boîtier (net) Vol. del alojamiento (neto) 箱體容量 (淨)	28 Lit. (1.0 cu.ft)	20 Lit. (0.7 cu.ft)	15 Lit. (0.5 cu.ft)	28 Lit. (1.0 cu.ft)	20 Lit. (0.7 cu.ft)

推奨ボックス：シールドタイプ
 Recommended Enclosure: Sealed type
 Boîtier recommandé: de type scellé

Alojamiento recomendado: Sellado
 推薦箱體：封閉型

Thiele/Small-Parameter
Thiele/Small-parametrar
Thiele/Small parameters

Parâmetros "Thiele/Small"
Parametri "Thiele/Small"
Thiele/Small parametry

Παράμετροι Thiele/Small
Thiele/Small параметры

	XS-L1236	XS-L1036	XS-L836	XS-L1246	XS-L1046
Impedanz , Impedans , Impedantie , Impedância , Impedenza , Impedancja , Αντίσταση , Сопротивление	4Ω	4Ω	4Ω	4Ω	4Ω
d (mm)	260	210	165	260	210
d (inch)	10.3	8.3	6.5	10.3	8.3
Rdc (Ω)	3.3	2.8	3.6	3.2	2.8
Fs (Hz)	25.6	25.4	33.85	26.1	26.8
Qts	0.36	0.33	0.45	0.37	0.36
Qes	0.39	0.35	0.48	0.40	0.39
Qms	5.18	4.69	7.26	5.11	4.96
Vas (Lit.)	66.1	51.6	14.9	56.3	47.7
Vas (Cu.ft)	3.67	1.75	0.61	3.67	1.75
Mms (g)	226.0	130.7	95.6	253.4	129.2
Lvc (mH)	1.2	1.2	1.3	1.3	1.2
Xmax (mm)	5	4.3	5.3	5	4.3
Xmax (inch)	0.2	0.17	0.21	0.2	0.17
BL (Tm)	17.5	13.0	12.4	18.4	12.6
Gehäusevol. (netto) Lādvolym (net) Inhoud behuizing (netto) Vol. da caixa (Líquido) Volume del contenitore (netto) Pojemność obudowy (netto) Όγκος κάσας (καθ.) Объем камеры (нетто)	28 Lit. (1.0 cu.ft)	20 Lit. (0.7 cu.ft)	15 Lit. (0.5 cu.ft)	28 Lit. (1.0 cu.ft)	20 Lit. (0.7 cu.ft)

Empfohlenes Gehäuse: Abgeschirmt
Rekommenderad låda: Förseglad typ (sealed)
Aanbevolen behuizing: Gesloten
Tipo de caixa recomendada: Selada

Tipo di contenitore consigliato: A tenuta
Zalecana obudowa: Typ zamknięty
Συνιστώμενη κάσα: Κλειστού τύπου
Рекомендуемая камера: Изолированного типа